

ELAC
Concentro S 503.2


ELAC The life of sound.

Defining the
future of sound.




ELAC Concentro S 503.2

The name Concentro signifies the extraordinary in every respect. The compact Concentro S 503.2 masterfully delivers the 'wow factor' from a surprisingly small package.



AS-XR technology

Unique, eye-catching, and acoustically ideal: the crystalline shape of the membrane provides the perfect balance of stiffness and damping.



Modern Hybrid Design

The progressive design elements from the Concentro Series combine with the clean lines of the Vela Series to create a strong visual presence.



StepX-JET

Since no two rooms are the same, midrange directivity can be adjusted using the exchangeable DCRs supplied.

Be in no doubt, the S 503.2 is a true Concentro in every respect. Design features and technical details that drove the success of the S 507 and S 509 are now combined in compact dimensions. The trapezoid basic shape, convex shaped baffle, and gently angled cabinet combine in a strikingly organic way to create a strong visual statement.

The extensive list of patented features and the revised woofer magnet system guarantee superlative sound. The effortless performance can be adjusted to suit the room acoustics. Close your eyes and you'll instantly forget you're listening to a compact speaker ... all you hear is music.

The Concentro S 503.2 is available in black and white high-gloss finishes and in high-gloss walnut veneer. The LS 100 stand specially developed for the Concentro S 503.2 is an available option.

ELAC

Concentro S 503.2

CONCENTRO S 503.2

| | |
|-------------------------------------|---|
| Height | 400 mm |
| Width | 225 mm |
| Depth | 372 mm |
| Weight | 13.4 kg |
| Type | 3-way, bass reflex |
| Woofers | 1 x 180 mm Ø, AS-XR cone |
| Midrange | 1 x 50 130 mm Ø, AS-XR AL cone |
| Tweeter | JET 6 |
| Crossover frequency | 400 2600 Hz |
| Nominal/peak power handling | 120 W 200 W |
| Minimum impedance | 4.8 Ω bei 120 Hz |
| Peak power handling | 400 W |
| Sensitivity | 87 dB / 2.83 V / m |
| Suitable for amplifiers from ... to | 4 – 8 Ω |
| Nominal impedance | 4 Ω |
| Recommended amplifier power | 60 – 500 W / channel |
| Finishes | High-Gloss Black Lacquer, High-Gloss White Lacquer High-Gloss Walnut Veneer |
| Accessories | Bi-Wiring-jumper set, 3 DCR (Directivity Control Ring) |


CONCENTRO

