

A masterpiece.

CONCENTRO



CONCENTRO

## ELAC Concentro 2.0

One look tells you this is no ordinary loudspeaker. The sophisticated front baffle features curves that allow optimum propagation and dispersion of sound waves from the two drivers.



**Sophisticated aluminum woofers**  
Through the use of aluminum, resonances that affect the linearity of common paper cones can be placed beyond the driver's operating frequency range.



**Crystal membrane midrange and mid-bass drivers**  
The eye-catching surface of the crystal membrane is more than just an attractive design feature. The midrange/woofers of the Concentro employs the Crystal Membrane.



**VX-JET 6 Tweeter**  
Delivering true high-definition sound, ELAC's JET 6 tweeter enralls with its lightning-fast response and wide dynamic range.

The Concentro 2.0 cannot be mistaken for any other speaker, with a complex base machined from a single block of aluminum and weighing more than 55 pounds. Integral oval side panels of precious wood, carbon fiber or leather surround a pair of side-firing 250mm woofers on either side of the enclosure. These newly-developed units feature smooth, stiff aluminum-sandwich diaphragms, and fire in a push-push / pull-pull configuration that delivers maximum energy and accuracy, down to the lowest octave. The back of the cabinet features twin ports for the bass drivers.

## CONCENTRO 2.0

Height	1680 mm with spikes
Width	460 mm with base
Depth	610 mm with base
Weight	152 kg
Type	4-Way, bass reflex
Woofer	4 x 250 mm Ø AS cone
Low-Midrange	1 x 220 mm Ø AS XR cone
High-Midrange	1 x 70 / 140 mm Ø, AS XR ring radiator
Tweeter	JET 6
Crossover frequency	120   360   2700 Hz
Nominal power handling	400 W
Minimal impedance	3,0 Ω at 620 Hz
Peak power handling	600 W
Frequency range (IEC 268-5)	18 – 50000 Hz
Sensitivity	90 dB/2,83 V/m
Suitable for amplifiers from ... to	4 – 8 Ω
Nominal impedance	4 Ω
Recommended amplifier power	80 - 600 W/channel
Finishes	Black High Gloss, White High Gloss
Accessories included in delivery	bi-wiring set, gloves, tool set, trolley

## CONCENTRO M 2.0

Height	1450 mm mit Spike
Width	460 mm with base
Depth	535 mm with base
Weight	90 kg
Type	3-Way, bass reflex
Woofer	4 x 220 mm Ø AS, cone
Midrange	1 x 70 / 140 mm Ø, AS XR ring radiator
Tweeter	JET 6
Crossover frequency	180   2700 Hz
Nominal power handling	300 W
Minimal impedance	2,8 Ω at 380 Hz
Peak power handling	300 W
Frequency range (IEC 268-5)	24 – 50000 Hz
Sensitivity	88 dB/2,83 V/m
Suitable for amplifiers from ... to	4 – 8 Ω
Nominal impedance	4 Ω
Recommended amplifier power	80 - 600 W/channel
Finishes	Black High Gloss, White High Gloss
Accessories included in delivery	bi-wiring set, gloves, tool set

CONCENTRO

<sup>(M)</sup>  
CONCENTRO

