



THE EVOLUTION OF DEBUT

DEBUT REFERENCE 3.0


The Debut Reference Series builds upon the success of Debut 3.0 with redesigned driver technology, refined cabinet construction, and a true 3-way floorstanding architecture engineered for greater clarity and control.

Retaining the proven tweeter and phase plug design while introducing newly developed single-cone aramid fiber woofers, Debut Reference delivers tighter bass response, cleaner midrange performance, and a more balanced overall presentation while combining acoustic performance with elevated craftsmanship and design.



ELAC Electroacoustic GmbH
Fraunhoferstraße 16
24118 Kiel - Germany
www.elac.de

ELAC Americas Inc.
1938 N. Batavia Street Suite K
Orange CA - 92865 USA
www.elac.com



ALUMINUM DOME TWEETER

The aluminum dome tweeter with phase plug delivers clear, detailed highs with wide dispersion and low distortion for an immersive listening experience.



ARAMID FIBER WOOFERS

Newly designed aramid fiber woofers provide tight, controlled bass and exceptional midrange clarity. The single-cone construction enhances stiffness, reduces distortion, and improves driver integration.



STITCHED LEATHER ACCENT

A stitched synthetic leather top panel adds a refined furniture-inspired aesthetic, distinguishing Debut Reference from conventional loudspeaker designs while complementing the premium cabinet finishes.

TECHNICAL SPECIFICATIONS


MODEL	DFR53	DBR63	DCR53
SPEAKER TYPE	3-WAY BASS REFLEX	2-WAY BASS REFLEX	2-WAY SEALED*
DRIVER CONFIGURATION	1" ALUMINUM DOME TWEETER 1 x 4" ARAMID FIBER MIDRANGE 2 x 5.25" ARAMID FIBER WOOFERS	1" ALUMINUM DOME TWEETER 1 x 6.5" ARAMID FIBER WOOFER	1" ALUMINUM DOME TWEETER 2 x 5.25" ARAMID FIBER WOOFERS
FREQUENCY RANGE (-3dB)	43 Hz - 34 kHz	49 Hz - 34 kHz	75 Hz - 34 kHz
SENSITIVITY (2.83v/m)	87dB	86.5dB	87.5dB
NOMINAL IMPEDANCE	6 Ω	6 Ω	6 Ω
CROSSOVER FREQUENCY	550 / 2150 Hz	2500 Hz	2550 Hz
RECOMMENDED AMPLIFIER POWER	30 - 150 W	20 - 140 W	30 - 120 W
NOMINAL / PEAK POWER HANDLING	80 / 130W	60 / 80 W	60 / 100W
H x W x D (mm)	1016 x 202 x 242	359 x 222 x 275	202 x 482 x 242

* DCR53 center channel utilizes a sealed enclosure design for flexible placement against rear walls or inside cabinetry.

AVAILABLE COLOURS



BLACK
BLACK TRIM




WHITE
TITANIUM TRIM



GREEN
BLACK TRIM



TITANIUM
TITANIUM TRIM



WALNUT
CHAMPAGNE TRIM



ELAC Electroacoustic GmbH
Fraunhoferstraße 16
24118 Kiel - Germany
www.elac.de

ELAC Americas Inc.
1938 N. Batavia Street Suite K
Orange CA - 92865 USA
www.elac.com