

WALL MOUNTED

Sound with Style and Strength

Introducing the new ELAC Muro and Muro Pro Outdoor/Indoor Speaker, where modern design meets exceptional versatility. Featuring a clean, sleek profile with no large visible knobs, this speaker seamlessly integrates into any environment, indoors or outdoors. Engineered for durability, it boasts an IP66 rating to withstand the elements, while removable port plugs allow you to transform its design into a ported configuration for enhanced bass performance when weather conditions permit. With its refined aesthetics and innovative functionality, the Muro Outdoor/Indoor Speaker is the perfect blend of style, adaptability, and premium sound quality.

PRODUCT DETAILS



Custom Design

ELAC Muro Outdoor/Indoor Speaker: a sleek, IP66-rated design offering weather-proof durability, adaptable bass performance, and premium sound, perfect for any indoor or outdoor space.



Custom Woofer


Custom polypropylene (PP) woofer, designed for outdoor IP66-rated speakers to deliver powerful, weatherproof performance in any environment.



Custom Tweeter

Enjoy crystal-clear highs with our 1" soft dome tweeter, engineered for outdoor IP66-rated speakers to provide precise, weatherproof audio performance.





Muro Series

Modern Design • Versatility

Watertight Wire Grommet – Features a durable rear

plastic cover that conceals wiring and provides IP66-rated protection, ensuring a clean installation and robust weather resistance.



uted audio sy

Flexible Wall/Ceiling Mount — The Muro outdoor

speaker offers exceptional versatility and flexibility with its supplied bracket, allowing seamless vertical, horizontal, wall, ceiling, or corner mounting for any installation need.



Sleek and Unique Design

With no large knobs and internally mounted brackets, the clean design of this speaker is both stylish and functional. The guided shoulder mount system ensures effortless installation while maintaining a streamlined, modern look that stands out in any setting.



• Adjustable 70/100 Volt Tap – easily select the desired wattage to optimize power

levels for your speaker in distributed audio systems



Removable Port Plugs – Designed for IP66-rated

outdoor use, this speaker features removable port plugs that allow you to switch between a sealed configuration for maximum weather resistance and a ported configuration to enhance bass performance when conditions permit. Transform the



design into a ported configuration for enhanced bass performance when weather conditions permit.


 Adjustable Angles – Shoulder mount has markings in 15 degress increments facilitating alignment of multiple speakers.



 Rotating Logo – The logo is designed to rotate, allowing seamless mounting in either vertical or horizontal orientations.










Muro Series

Modern Design • Versatility

SERIES	MURO	MURO PRO	MURO	MURO PRO
MODEL	OD-M61	OD-M61T	OD-M81	OD-M81T
SPEAKER TYPE	2-WAY SEALED/PORTED DESIGN			
FREQUENCY RESPONSE -3 dB:	80 то 20Кнz		70 то 20Кнz	
FREQUENCY RESPONSE -6 dB:	65 то 20Кнz		55 to 20KHz	
TRANSFORMER TAP		100V 8Ω, 30W, 15W, 7.5W 3.8W (70V)		100V 8Ω, 60W, 30w, 15W 7.5 (70V)
NOMINAL IMPEDANCE	8 Ω		8Ω ±20% @ LOW-Z	
SENSITIVITY @2.83 V/1M	86 dB		87 dB	
CROSSOVER FREQUENCY	2160 Hz			
RECOMMENDED AMPLIIFER POWER	30 - 100 W		30 - 180 W	
NOMINAL/PEAK POWER HANDLING	80/130 W		100/150 W	
TWEETER	25mm Silk Dome Tweeter with 2-layer Copper-Clad Aluminum Voice Coil			
WOOFER (ARAMID-FIBER)	6 ½ " 25MM POLYPROPYLENE CONE, RUBBER SURROUND		8 " 25mm polypropylene cone, rubber surround	
CABINET	UV-Resistant Plastic			
CABINET FINISH	Black - White			
PORT	Sealed with Option for Ported Design			
SPEAKER CONNECTION	5 - Way Binding Posts		4 Position Euroblock	
WIDTH (IN / MM)	7.87/200		9.84/250	
HEIGHT (IN / MM)	12.2/310		15.35/390	
DEPTH (IN / MM)	9.25/235		11.2/285	
Net Weight (lbs / KG)	7.71/3.5		11.02/5.0	







Muro Series

Modern Design • Versatility





