


Inherently modern,
discretely powerful.



ELAC Subwoofer SUB 2070.2

Established, prestigious but certainly not pretentious: The ELAC SUB 2070.2 proves that some things justifiably endure. This bestselling model offers new features that allow everyone to enjoy flawless bass reproduction.



Everything under control

The new ELAC Sub Control 3.0 app puts acoustic optimization at your fingertips, letting you easily adjust acoustic parameters or launch Auto EQ room correction from your listening position.



Powerful drive

Generously dimensioned and extremely robust drive units combined with the muscular power amplifier to deliver astonishing depth, precision, and authority – in every situation!



Potent performance

Combining the efficiency of modern amplifier concepts with the sound quality of class A/B designs, BASH® technology delivers high output power for impressive performance.

The elegant, unobtrusive design of the SUB 2070.2 deliberately reveals little about the technical features and possibilities that lurk within this subwoofer. Sleek, high-gloss laquered surfaces uncluttered by technical elements immediately draw the eye and ensure that the unit blends seamlessly with every interior decor.

However, the SUB 2070.2 also knows how to impress in terms of acoustic performance. Two 10" drive units are responsible for converting the electric signals delivered from a 600-Watt power amplifier using BASH® technology. They are installed opposite one another in an impulse-compensating configuration that perfectly cancels the mechanical forces inside the sealed cabinet, leaving nothing but perfectly generated airborne sound. No vibrations ... just pure sound!

Enjoy the convenience of app-based control with extensive functions such as automatic calibration or a parametric equalizer. Smart operation, smart design: The SUB 2070.2 is not just any loudspeaker for low-frequency signals – it is the perfect choice in every sense!

ELAC Subwoofer

SUB 2070.2

TECHNICAL SPECIFICATIONS

SUB 2070.2

Height x Width x Depth	475 x 360 x 385 mm
Weight	32 kg
Type	Active, 2 Woofers in closed cabinet, Push-Push/Pull-Pull
Woofers	2 x 250 mm Ø, AS
Frequency range (IEC 268-5)	18 – 180 Hz
Max. amplifier power	600 W
Crossover frequency	40 – 150 Hz
Finishes	Black High Gloss, White High Gloss

